

Product data sheet

GC 302



Radar movement detector for the activation of automatic doors

AREAS OF APPLICATION

- Activation of automatic swing, sliding, folding, revolving and curved sliding doors
- Interior and exterior doors

PRODUCT FEATURES

- Convenient commissioning with pre-programmed settings
- Configuration possible via push buttons or remote control
- Clearly defined radar field (narrow or wide field) with reliable detection
- Integrated motion tracking also records slow movements
- Movement direction detection and cross-traffic fade-out reduces energy consumption in the building
- Door opening impulse only triggered if needed

TECHNICAL DATA

Productname	GC 302
Dimensions	176 x 62 x 52 mm
Technology	Electromagnetic radar waves
Operating voltage	12-36 V DC / 12-28 V AC
Operating current	50 mA
IP rating	IP54
Cable connection type	Plug-in screw terminal
Connector cable length	5000 mm
Installation height (max.)	4000 mm
Transmission frequency	24.125 GHz
Weight	150 g
Service temperature	-20 – 60 °C
Humidity	0-90 % relative, non-condensing

VARIANTS / ORDER INFO

Designation

GC 302 R radar movement detector

GC 302 R radar movement detector

ACCESSORIES

CEILING INSTALLATION KIT GC 302

Installation kit for integrating the detector in the ceiling



Designation

Ceiling installation kit GC 302

WEATHER HOOD GC 302

Protects the sensor when installed outdoors



Designation

Weather hood GC 302
