Product data sheet

IQ lock M DL *

Mechanical panic lock for simple panic functions on double leaf doors

AREAS OF APPLICATION

- → Double leaf emergency exit and panic doors (left hand and right hand door)
- → Doors along escape and rescue routes
- → Fire and smoke protection doors

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-14T03:56:52Z

IQ lock M DL *

PRODUCT FEATURES

- Mechanical self-locking ensures automatic deadbolt projection every time the door is closed
- Unlocking of active leaf by activating passive leaf (full panic function)
- Divided cross latch prevents the bolt from locking even under side-load
- Small rear backset and small dimensions of the lock case
- Can be combined with electronic thumbturn cylinders

TECHNICAL DATA

Productname	IQ lock M DL *
DIN direction	left / right
Service temperature	-10 - 50 °C
Panic function / mechanical self-locking	Yes
Divided cross latch (3 mm gap between latch and bolt)	Yes
Resistant to forcing	10000 N

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Distance lock	Backset	DIN direction
IQ lock M DL *	for solid leaf doors ; with round face plate 20 x 235 x 3 mm	133889	72 mm	65 mm	left / right
IQ lock M DL *	for tubular-framed doors ; with rectangular face plate 22 x 285 x 3 mm	157383	92 mm	35 mm	left / right
IQ lock M DL *	for tubular-framed doors ; with rectangular face plate 24 x 270 x 3 mm	133886	92 mm	40 mm	left / right
IQ lock M DL *	for tubular-framed doors with rectangular face plate 24 x 285 x 3 mm	161341	92 mm	35 mm	left / right
IQ lock M DL *	for solid leaf doors ; with round face plate 24 x 235 x 3 mm	163835	72 mm	65 mm	left / right
IQ lock M DL *	for tubular-framed doors ; with rectangular face plate 28 x 270 x 3 mm	162645	92 mm	35 mm	left / right
IQ lock M DL *	for tubular-framed doors ; with rectangular face plate 24 x 270 x 3 mm	133887	92 mm	45 mm	left / right
IQ lock M DL *	for tubular-framed doors ; with rectangular face plate 24 x 270 x 3 mm	133885	92 mm	35 mm	left / right

IQ lock M DL *

ACCESSORIES

STRIKE BOX SOLID LEAF *

Mechanical strike box as passive leaf rod locking element on double leaf doors

Designation	Description	Ident-No.	DIN direction	Backset	EAN
Strike box solid leaf doors *	Without face plate, distance of the screw points for locking bolts: 211 mm / the vertical locking bolts are positioned on; backset - 25mm positioned; (starting from handle)	133904	left / right	60 mm	4042938339049
Strike box solid leaf doors *	Without face plate, distance of the screw points for locking bolts: 211 mm / the vertical locking bolts are positioned on; backset - 25mm positioned; (starting from handle)	133903	left / right	55 mm	4042938339032
Strike box solid leaf doors *	Without face plate, distance of the screw points for locking bolts: 211 mm / the vertical locking bolts are positioned on; backset - 35mm; (starting from handle)	133908	left / right	100 mm	4042938339087
Strike box solid leaf doors *	Without face plate, distance of the screw points for locking bolts: 211 mm / the vertical locking bolts are positioned on; backset - 35mm; (starting from handle)	133907	left / right	80 mm	4042938339070
Strike box solid leaf doors *	Without face plate, distance of the screw points for locking bolts: 211 mm / the vertical locking bolts are positioned on; backset - 35mm; (starting from handle)	133905	left / right	65 mm	4042938339056
Strike box solid leaf doors *	Without face plate, distance of the screw points for locking bolts: 211 mm / the vertical locking bolts are positioned on; backset - 35mm; (starting from handle)	133906	left / right	70 mm	4042938339063

TUBULAR FRAME STRIKE BOX *

Mechanical strike box as passive leaf rod locking element on double leaf doors

Designation	Description	Ident-No.	DIN direction	Backset	EAN
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152249	left / right	45 mm	4042938522496
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152251	left / right	70 mm	4042938522519
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152248	left / right	35 mm	4042938522489

IQ lock M DL *

Designation	Description	Ident-No.	DIN direction	Backset	EAN
Strike box tubular-framed doors, short *	Without face plate, distance of the screw points for locking bolts: 267 mm / the vertical locking bolts are positioned on backset	152250	left / right	60 mm	4042938522502

STRIKE BOX TUBULAR FRAME DOORS, LONG *

Mechanical strike box as passive leaf rod locking element on double leaf doors

Designation	Description	Ident-No.	DIN direction	Backset	EAN
Strike box tubular-framed doors, long *	Without face plate, for the use of safety fittings, distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset	133899	left / right	35 mm	4042938338998
Strike box tubular-framed doors, long *	Without face plate, for the use of safety fittings, distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset	133900	left / right	40 mm	4042938339001
Strike box tubular-framed doors, long *	Without face plate, for the use of safety fittings, distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset	133902	left / right	55 mm	4042938339025
Strike box tubular-framed doors, long *	Without face plate, for the use of safety fittings, distance of the screw points for locking bolts: 323 mm / the vertical locking bolts are positioned on backset	133901	left / right	45 mm	4042938339018

LIPPED STRIKE PLATE TOP LOCK *

Keeper for top lock

Designation	Description	Ident-No.	Colour	Dimensions	DIN direction
Lipped strike plate top lock *	for tubular-framed doors, rectangular / DIN left / right,; 22 x 54 x 3 mm (core dimensions),; width with tab strike plate 26 mm,; with tongue 18.4 x 13 mm	162322	Stainless steel	22 x 54 x 3 mm	left / right
Lipped strike plate *	For the top locking of solid leaf doors; 20 x 100 x 3 mm (core dimensions); Width with tab strike plate 50 mm	133920	Stainless steel		left / right
Lipped strike plate top lock *	for solid leaf doors, round / DIN left / right,; 20 x 100 x 3 mm (core dimensions),; width with tab strike plate 40 mm,; with tongue 20.4 x 16 mm	161532	Stainless steel	20 x 100 x 3 mm	left / right

IQ lock M DL *

BOTTOM-CLOSING RECESS *

Keeper for rod locking downward

Designation	Description	Ident-No.	Dimensions	DIN direction	Type of installation
Bottom-closing recess *	For holding the locking bolt down;; 100 x 56 x 20 mm	133919	100 x 56 x 21.5 mm	left / right	Floor

TOP LOCK TOP *

Rod locking guide upwards

Designation	Description	Ident-No.	Dimensions	EAN
Top lock top *	Top lock for securing the self-locking mechanism / Face plate 20 x 54 x 3 mm, round	133922	20 x 54 x 3 mm	4042938339223
Top lock top *		157391		4042938573917

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.