

Product data sheet

Perlan 140 set for glass leaves



Sliding door fitting for wall installation and glass leaf

AREAS OF APPLICATION

- For wall installation
- For leaf weights up to 80 kg
- For glass leaves with a 30 mm glass clamping plate



Perlan 140 set for glass leaves

PRODUCT FEATURES

→ Sliding door fitting for wall installation and glass leaf with leaf weight up to 80 kg

TECHNICAL DATA

Productname	Perlan 140 set for glass leaves
Corrosion protection class	2
Glass thickness	8 - 12.76 mm
Colour	EV1

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Leaf width (min.)	Leaf width (max.)
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134860	Stainless steel optic	575 mm	1000 mm
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134855	EV1	900 mm	1240 mm
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134861	Stainless steel optic	900 mm	1240 mm
Perlan 140 set for glass leaves	For wall attachment with concealed wall bracket, glass clamping plate individually covered and Perlan SoftStop, up to 80 kg leaf weight. For 2050 mm track length Perlan SoftStop one-sided, for 2450 mm track length Perlan SoftStop both sides.	134854	EV1	575 mm	1000 mm

Perlan 140 set for glass leaves

PART

FLOOR GUIDE FOR GLASS LEAF

Floor guide with variable adjustment for glass thicknesses 8, 10 and 12 mm



Designation	Description	Ident-No.	Colour	Glass thickness
Floor guide for glass leaf (adjustable)	with variable adjustment for glass thickness 8–13.5 mm, with frieze band for noise reduction with structured glass surfaces, without attachment material	120417	silver-coloured	8 – 13.5 mm

END STOP PERLAN 140 (ALSO KS)

End stop for sliding leaves also suitable for outdoor use



Designation	Description	Ident-No.	Colour
End stop Perlan 140 (also KS)	Steel parts made of stainless steel	119362	white

PERLAN SOFTSTOP SET, SHORT VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 575 to 900 mm




Designation	Description	Ident-No.	Leaf width (min.)	Leaf width (max.)
Perlan SoftStop set, short, one side	The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate	128876	575 mm	900 mm

Perlan 140 set for glass leaves

WALL BRACKET CONCEALED PERLAN

Wall bracket for concealed wall installation of tracks



Designation	Description	Ident-No.	Colour
Wall bracket concealed Perlan	for use up with to 37 mm leaf thickness	130463	Stainless steel optic
Wall bracket concealed Perlan	for use up with to 37 mm leaf thickness	130466	Stainless steel optic
Wall bracket concealed Perlan	for use up with to 37 mm leaf thickness	130414	EV1
Wall bracket concealed Perlan	bespoke, for use with up to 37 mm leaf thickness	130462	EV1
Wall bracket concealed Perlan	bespoke, for use with up to 37 mm leaf thickness	130468	Stainless steel optic

TRACK PERLAN 140

Track for sliding door fitting



Designation	Description	Ident-No.	Colour
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142518	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128660	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	128662	Stainless steel optic
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135048	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135047	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	142519	EV1
Track Perlan 140	with countersunk drill holes (prepared for Perlan SoftStop)	135046	EV1