

Product data sheet GC GR for GC 338



Sensor roller guide rail Powerturn for GC 338 sensor strip

AREAS OF APPLICATION

- ightarrow Suitable for single and double leaf swing doors
- ightarrow Suitable for the GEZE Powerturn drive series
- ightarrow For attaching sensor strips



PRODUCT FEATURES

- ightarrow Specialised roller guide rail to which sensor strips can be attached
- ightarrow Visually looks like a single construction component and therefore fulfils the highest design requirements
- ightarrow Can be mounted together with the safety components on narrow door profiles
- ightarrow The roller guide rail and sensor are mounted on the same level and do not cover glass cut-outs on glass doors
- ightarrow Can also be retrofitted on existing door systems
- ightarrow Rain cover optionally available

TECHNICAL DATA

Productname	GC GR for GC 338

VARIANTS / ORDER INFO

Designation	Description	ldent- No.	Colour	Type of installation	
GC GR for GC 338 Powerturn	For Powerturn / Powerturn F, installation on the hinge side, lever length 330 mm	157451	according to RAL	Transom installation hinge side	
GC GR for GC 338 Powerturn	For Powerturn / Powerturn F, installation on the opposite hinge side, lever length 450 mm	157476	EV1	Transom installation opposite hinge side	
GC GR for GC 338 Powerturn	For Powerturn / Powerturn F, installation on the opposite hinge side, lever length 450 mm	157477	according to RAL	Transom installation opposite hinge side	
GC GR for GC 338 Powerturn *	For Powerturn / Powerturn F, installation on the opposite hinge side, lever length 450 mm	157475	according to RAL	Transom installation opposite hinge side	
GC GR for GC 338 Powerturn	For Powerturn / Powerturn F, installation on the hinge side, lever length 330 mm	157472	EV1	Transom installation hinge side	
GC GR for GC 338 Powerturn	For Powerturn / Powerturn F, installation on the hinge side, lever length 330 mm	157450	EV1	Transom installation hinge side	
GC GR for GC 338 Powerturn	For Powerturn / Powerturn F, installation on the opposite hinge side, lever length 450 mm	157474	EV1	Transom installation opposite hinge side	
GC GR for GC 338 Powerturn	For Powerturn / Powerturn F, installation on the hinge side, lever length 330 mm	157473	according to RAL	Transom installation hinge side	



ACCESSORIES

GC 338

Sensor strip with standby mode for the protection of automatic swing and revolving doors

Designation	Description	ldent- No.	Colour	Output	Operating voltage
GC 338 Pair of sensor strips 1200 mm	consisting of two complete sensor strips for protection of the swivelling range of automatic swing and revolving doors in accordance with DIN 18650 / EN 16005	142825	according to RAL	Electrical relay	24 V DC +/- 20%
GC 338 Pair of sensor strips 1500 mm	consisting of two complete sensor strips for protection of the swivelling range of automatic swing and revolving doors in accordance with DIN 18650 / EN 16005	142827	according to RAL	Potential-free relay contact	24 V DC +/- 20%
GC 338 Pair of sensor strips 1500 mm	consisting of two complete sensor strips for protection of the swivelling range of automatic swing and revolving doors in accordance with DIN 18650 / EN 16005	142757	EV1	Electrical relay	24 V DC +/- 20%
GC 338 Pair of sensor strips 1200 mm	consisting of two complete sensor strips for protection of the swivelling range of automatic swing and revolving doors in accordance with DIN 18650 / EN 16005	142219	EV1	Electrical relay	24 V DC +/- 20%