

Product data sheet GC 342 / GC 342+ fire protection adapter *



Necessary for laying the connection cable hinge side/opposite hinge side with drill hole diameters of 5 mm

AREAS OF APPLICATION

- → Accessories for the GC 342 / GC 342+ laser scanner
- → For fire protection doors, please consult the door manufacturer concerning the permission prior drilling
- \rightarrow Compatible with GC 342+ if both it and a drive are mounted on the opposite hinge side.
- → GC 342 and GC 342+ can be combined if the activation function of the GC 342+ is not needed.

GC 342 / GC 342+ fire protection adapter *



PRODUCT FEATURES

- → Insertable interface board
- → Master-slave replacement cable for GC 342 / GC 342+

TECHNICAL DATA

Productname GC 342 / GC 342+ fire protection adapter *

VARIANTS / ORDER INFO

Designation	Description	Ident-No.
GC 342 fire door adaptor	Including door connection cable BS/BGS. Reduces the necessary borehole diameter from 10 mm to 5 mm	189384

GEZE GmbH Reinhold-Vöster-Straße 21–29 D-71229 Leonberg TEL +49 7152 203-0 WEB www.geze.de Mail info.de@geze.com 2024-03-30T03:59:06Z

^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.